

FARM MACHINERY

Domries

SINCE 1924

STEEL FABRICATION

WHEEL TYPE

OFFSET DISC HARROWS

SERIES OFXSL

Medium
Stubble Disc

**CUT
WIDTHS
12'1"
TO
18'2"**



OPTIONS

- ★ BLADE CLEANERS
- ★ BLADE EDGE & THICKNESS
- ★ DURA FACED BLADES
- ★ BOLT ON FURROW FILLER
- ★ BOLT ON REAR UTILITY HITCH
- ★ BOLT ON BLADE EXTENSIONS
- ★ HOSE KIT
- ★ TRUNION MOUNTED TAPERED ROLLER BEARINGS, FOR 1¾ sq.
- ★ GANG BOLT

DOMRIES ENTERPRISES, INC.

12281 Road 29
Madera, California
Phone (559) 673-9143
Fax (559) 673-4110

<http://www.domriesentinc.com>



The Deluxe Disc

SPECIFICATIONS

OFXSL

MODEL ORDER NO.	A.S.A.E. WIDTH OF CUT	NO. OF BLADES	NO. OF BEARINGS MACHINE	WORKING WEIGHTS			APPROX. DRAWBAR POWER		
					PER BLADE	PER FT.	H.P. 4 M.P.H.	H.P. 6 M.P.H.	LBS. PULL
OFXSL-1212-2422	12'5"	24	8	8483	353	706	141	213	7634
OFXSL-1212-2622	13'3"	26	8	8835	339	679	150	228	7951
OFXSL-1212-2822	14'3"	28	8	9361	334	668	162	245	8424
OFXSL-1212-3022	15'3"	30	10	10009	333	627	174	262	9008
OFXSL-1212-3222	16'2"	32	12	10440	326	652	184	280	9396
OFXSL-1212-3422	17'2"	34	12	10996	323	646	196	297	9896
OFXSL-1212-3622	18'2"	36	12	11411	410	633	208	314	10269

FEATURES

BEARINGS GREASEABLE BALL BEARINGS IN HEAVY CAST FRAME. SELF ALIGNING. TRIPLE LIP SEAL.

GANG RODS 1 3/4" SO. HI CARBON STEEL.

WHEEL BEARINGS HEAVY 8000 LB. RATED HUBS MFG. BY DOMRIES WITH TWO GREASE SEALS AND A GREASE BARRIER. AXLES ARE SLIP IN TYPE WITH LOCKING CROSS BOLT. SEAL WEAR SLEEVES ARE REPLACEABLE AND ELIMINATE WEAR ON AXLE.

DISC BLADES HIGH QUALITY BLADES WITH CROSS ROLLED STEEL MFG. IN THE U.S.A. 32. x 5/16 NOTCHED BLADES IS STD. EQUIPMENT.

BLADE SPACING 12"

GANG BEAMS THREE 3 1/2" SO. HEAVY WALL TUBES.

DUAL WHEELS 16 x 10" x 8 BOLT WHEELS WITH 16 x 12.5 SL TIRES DETERMINED BY SIZE AND MODEL OF MACHINE.

HYDRAULICS 4" BORE WITH 16" STROKE.

HITCH A SERIES OF HOLES IN THE DOUBLE HITCH PLATES ALLOWS FAST ONE BOLT OFFSET ADJUSTMENT. THE SINGLE TUBE DESIGN PERMITS SHORTER TURNS BEHIND DUAL WHEEL TRACTORS.

TONGUE JACK STD. EQUIPMENT CLAMP ON TYPE.

FRAME 4 x 8 STEEL TUBE BRACED AND ELECTRIC WELDED.

GANG ANGLE SET BARS ANGLES FROM 16° TO 30° WITH NON SLIP SET BARS AND DROP PINS.

LEVELING LINKAGE KEEPS DISC LEVEL IN ALL STAGES FROM DISCING TO TRANSPORT. EASY ADJUSTMENT TO TRACTOR HITCH HEIGHT IS MADE WITH FRONT OF FRAME TOP LINK. ALL SETTINGS ARE CUSHIONED FROM SHOCK BY TWO HEAVY COMPRESSION SPRINGS.

TRANSPORT SAFETY A HEAVY CROSS PIN TAKES ALL OF THE MACHINE WEIGHT OFF OF THE HYDRAULIC CYLINDER WHEN TRANSPORTING. DOMRIES SCISSOR LINKAGE ALLOWS FULL FREEDOM OF CYLINDER MOVEMENT WITHOUT DAMAGE TO DEPTH CONTROL WHEN NOT IN USE PIN HAS STORAGE RACK.

TONGUE A SINGLE PIECE OR CLEVIS "U" TONGUE IS AT YOUR OPTION.

★ DOMRIES RESERVES THE RIGHT TO MAKE CHANGES AND/OR IMPROVEMENTS IN DESIGN AND CONSTRUCTION OF PARTS OR MACHINES SHOWN HEREIN WITHOUT NOTICE OR OBLIGATION



DOMRIES ENTERPRISES, INC.

12281 Road 29

Madera, California 93638

Phone (559) 673-9143 .FAX (559) 673-4110

Visit our website @ <http://www.domriesentinc.com>

SOLD BY

