

DOMRIES ENTERPRISES, INC 12281 Road 29 Madera, California Phone (559) 673-9143 Fax (559) 673-4110 http://www.domriesentinc.com



The Deluxe Disc

## Dannes

## STANDARD FEATURES

BEARINGS TRIPLE SEALED BALL BEARINGS WITH TRUNION SELF ALIGNING BEARING HOLDERS.

GANG RODS 1 1/2" SQUARE HI CARBON STEEL.

DISC BLADES HI QUALITY BLADES WITH CROSS ROLLED STEEL 24 X 5mm IS STANDARD EQUIPMENT.

BLADE SPACING 9" SPACING IS STANDARD WITH HEAVY DUTY CAST IRON SPACING SPOOLS.

DUAL WHEELS 15" X 6" RIM WITH 6 BOLTS IS STANDARD.

TIRES 7.60 x 15 x 6 PLY IS STANDARD EQUIPMENT.

WHEEL BEARINGS HEAVY 5000 LB. RATED HUBS MFG. BY DOMRIES WITH TWO GREASE SEALS AND A GREASE BARIER. SPINDLES ARE EASY TO REPLACE SLIP IN TYPE WITH CROSS BOLT LOCK. WEAR SLEEVES ARE REPLACEABLE AND ELIMINATE WEAR ON SPINDLE.

HYDRAULICS 3 1/2 X 12" HI PRESSURE CYLINDER.

FRAME 4 X 4 HEAVY WALL SQUARE TUBULAR STEEL BRACED AND ELECTRIC WELDED.

LEVELING LINKAGE KEEPS DISC LEVEL IN ALL STAGES FROM DISCING TO TRANSPOST. EASY ADJUSTMENT TO TRACTOR HITCH HEIGHT IS MADE WITH TOP LINK AT FRONT OF FRAME. ALL SETTINGS ARE CUSHIONED FROM SHOCK BY TWO HEAVY COMPRESSION SPRINGS.

TRANSPORT SAFETY A HEAVY CROSS PINTAKES ALL OF THE MACHINE WEIGHT OFF OF THE HYDRAULIC CYLINDER WHEN TRANSPORTING. DOMRIES SCISSOR LINKAGE ALLOWS FULL FREEDOM OF CYLINDER MOVEMENT WITHOUT DAMAGE TO THE DEPTH CONTROLS WHEN NOT IN USE THE PIN HAS A STORAGE RACK.

GANG ANGLE SETTING FRONT GANG ANGLE IS SET WITH DOMRIES QUICK SET DROP PINS. REAR GANG ANGLE IS SET WITH A SINGLE CRANK FOR BOTH GANGS. POSITIVE NO WRENCH NO SLIP SETTING ALLOW ANGLE SET FROM 12° TO 28°.

DEPTH CONTROL SET BAR WITH CROSS PIN ALLOWS EXACT RETURN TO PRESET DEPTH OF CUT. ANOTHER PIN ALLOWS THE WHEELS TO BE RAISED OFF THE GROUND TO BE USED FOR ADDED CUTTING WEIGHT.



## HEAVYDUTYSERIESOTH





DEPTH CONTROL SET BAR WITH TRANSPORT SAFETY PIN IN PLACE. OPTIONAL CENTER SHANK AND SWEEP.



FRONT GANG ANGLE IS TYPICAL OF DOMRIES QUICK PULL PIN SETTING. POSITIVE MATCHED ANGLES WITH NON SLIP GANG SET PINS. NO WRENCHES NEEDED.



FRONT MOUNTED TURNBUCKLE ADJUSTS MACHINE LEVEL TO TRACTOR HITCH HEIGHT. LINKAGE WILL THEN KEEP MACHINE AT THE SAME LEVEL FROM DISCING TO TRANSPORT.

