

Section 13
SERIES OTL
ORCHARD TANDEM



TANDEM DISC HARROWS



ONE PASS ★ LEVEL PANEL ★ BALANCED CUT



OTL SERIES

**CUTTING WIDTHS
10'10" TO 16'11"**



DOMRIES ENTERPRISES, INC.
12281 Road 29
Madera, California 93638
Phone (559) 673-9143 • FAX (559) 673-4110
Visit Our Website @ <http://www.domriesentinc.com>

Domries

OTL TAN



FEATURES

BEARINGS TRIPLE SEALED BALL BEARINGS WITH TRUNION SELF ALIGNING BEARING HOLDERS

GANG RODS 1 1/8 SQUARE HI CARBON STEEL

DISC BLADES HI QUALITY INGERSOL BLADES WITH CROSS ROLED STEEL 22" X 8 GA. OR 24" X 7 GA. ARE STANDARD EQUIPMENT

BLADE SPACING 9" SPACING IS STANDARD WITH HEAVY DUTY CAST IRON SPACING SPOOLS

DUAL WHEELS 15" X 5 1/2" X 6 BOLT IS STANDARD

TIRES 7.60 X 6 PLY IS STANDARD EQUIPMENT

WHEEL BEARINGS HEAVY 5000 LB. RATED HUBS MFG. BY DOMRIES WITH TWO GREASE SEALS AND A GREASE BARRIER. SPINDLES ARE EASY TO REPLACE SLIP IN TYPE WITH CROSS BOLT LOCK. WEAR SLEEVES ARE REPLACEABLE AND ELIMINATE WEAR ON SPINDLE.

DEPTH CONTROL SET BAR WITH CROSS PIN ALLOWS EXACT RETURN TO PRESET DEPTH OF CUT. ANOTHER PIN ALLOWS GROUND TO BE USED FOR ADDED CUTTING WEIGHT.

HYDRAULICS 3 X 12 HI PRESSURE CYLINDER FRAME 3 X 3 HEAVY WALL SQUARE TUBE ELECTRIC WELDED.

LEVELING LINKAGE KEEPS DISC LEVEL TO TRANSPORT. EASY ADJUSTMENT TO MADE WITH TOP LINK AT FRONT OF FRAME CUSHIONED FROM SHOCK BY TWO HEAVY TRANSPORT SAFETY A HEAVY CROSS PIN WEIGHT OF OF THE HYDRAULIC CYLINDER DOMRIES SCISOR LINKAGE ALLOWS FULL MOVEMENT WITHOUT DAMAGE TO THE DISC **GANG ANGLE SETTING** FRONT GANG ANGLE QUICK SET DROP PINS. REAR GANG ANGLE CRANK FOR BOTH GANGS. POSITIVE NO ALLOW ANGLE SET FROM 12° TO 28°.

ORCHARD DEM SERIES



REAR GANG SETTING IS A QUICK & SIMPLE TURN OF A CRANK. BOTH GANGS ARE COUPLED TOGETHER IN POSITIVE MATCHED ANGLES FOR A SMOOTH AND LEVEL FINISH.



GANG ANGLE SETTING IS TYPICAL DOMRIES QUICK PULL PIN SETTING. POSITIVE MATCHED ANGLES WITH NON SLIP GANG BARS AND ALL WITH NO WRENCHES.



FRONT MOUNTED TURNBUCKLE ADJUSTS MACHINE LEVEL TO TRACTOR HITCH HEIGHT. LINKAGE WILL THEN KEEP MACHINE AT THE SAME LEVEL FROM DISCING TO TRANSPORT.



HEAVY CAST IRON SPOOLS. TRUNION SELF ALIGNING BEARINGS TRIPLE SEALED BALL BEARINGS. RUGGED STEEL BEARING BRACKET. A REAL WINNING COMBINATION



DEPTH CONTROL SET BAR WITH TRANSPORT SAFETY PIN IN PLACE. OPTIONAL CENTER SHANK AND SWEEP.

UNDER
TUBULAR STEEL BRACED AND


IN ALL STAGES FROM DISCING
TRACTOR HITCH HEIGHT IS
ME. ALL SETTINGS ARE
BY COMPRESSION SPRINGS.
TAKES ALL OF THE MACHINE
R WHEN TRANSPORTING.
FREEDOM OF CYLINDER
DEPTH CONTROL.

IS SET WITH DOMRIES
LE IS SET WITH SINGLE
WRENCH NO SLIP SETTINGS

OPTIONS

- BLADE CLEANERS
- UTILITY HITCH
- DRAG MTG. BRACKETS
- CENTER SHANK W/SWEEP
- HITCH JACK
- HOSE GUIDE
- HYD. HOSE KIT
- BLADE EXTENSIONS
- 1 1/4" TOOL BAR BRACKETS
- CLEVIS TONGUE


OTL DISC FEATURES



SINGLE TONGUE HITCH IS STANDARD.
DOUBLE LIP IS AN OPTION



HEAVY DUTY AXEL SHAFT WITH 4
LUBRICATABLE BEARINGS.



QUICK CHANGE SPINDLES HAVE TWO GREASE
SEALS AND REPLACEABLE WEAR SLEVES

SPECIFICATIONS

MODEL NUMBER	A.S.A.E. WIDTH OF CUT	SIZE BLADES	NO. BLADES	BLADE EDGE		SPACING		NO. BEAR	APPROX. REQ. P.T.O H.P.	APPROX. WT. LBS.
				FRONT	REAR	FRONT	REAR			
OTL-99-2820	10'10"	22"	28	SM	SM	9	9	12	50-70	3038
OTL-99-2821	10'10"	22"	28	SM	N	9	9	12	50-70	3022
OTL-99-2822	10'10"	22"	28	N	N	9	9	12	50-70	3008
OTL-99-2840	11'1"	24"	28	SM	SM	9	9	12	50-70	3214
OTL-99-2841	11'1"	24"	28	SM	N	9	9	12	50-70	3196
OTL-99-2842	11'1"	24"	28	N	N	9	9	12	50-70	3174
OTL-99-3220	12'4"	22"	32	SM	SM	9	9	12	60-80	3186
OTL-99-3221	12'4"	22"	32	N	SM	9	9	12	60-80	3171
OTL-99-3222	12'4"	22"	32	N	N	9	9	12	60-80	3157
OTL-99-3240	12'6"	24"	32	SM	SM	9	9	12	60-80	3389
OTL-99-3241	12'6"	24"	32	N	SM	9	9	12	60-80	3369
OTL-99-3242	12'6"	24"	32	N	N	9	9	12	60-80	3349
OTL-99-3620	13'9"	22"	36	SM	SM	9	9	16	70-90	3446
OTL-99-3621	13'9"	22"	36	N	SM	9	9	16	70-90	3424
OTL-99-3622	13'9"	22"	36	N	N	9	9	16	70-90	3402
OTL-99-3640	14'0"	24"	36	SM	SM	9	9	16	70-90	3674
OTL-99-3641	14'0"	24"	36	N	SM	9	9	16	70-90	3679
OTL-99-3642	14'0"	24"	36	N	N	9	9	16	70-90	3624
OTL-99-4020	15'3"	22"	40	SM	SM	9	9	16	80-95	3569
OTL-99-4021	15'3"	22"	40	N	SM	9	9	16	80-95	3545
OTL-99-4022	15'3"	22"	40	N	N	9	9	16	80-95	3521
OTL-99-4040	15'6"	24"	40	SM	SM	9	9	16	80-95	3822
OTL-99-4041	15'6"	24"	40	N	SM	9	9	16	80-95	3794
OTL-99-4042	15'6"	24"	40	N	N	9	9	16	80-95	3768
OTL-99-4420	16'8"	22"	44	SM	SM	9	9	16	85-100	3692
OTL-99-4421	16'8"	22"	44	SM	N	9	9	16	85-100	3676
OTL-99-4422	16'8"	22"	44	N	N	9	9	16	85-100	3648
OTL-99-4440	16'11"	24"	44	SM	SM	9	9	16	85-100	3970
OTL-99-4441	16'11"	24"	44	SM	N	9	9	16	85-100	3939
OTL-99-4442	16'11"	24"	44	N	N	9	9	16	85-100	3910

P.T.O. HORSE POWER AT 6 MI. PER HR. WITH 2 WHEEL DRIVE TRACTOR. 4 WHEEL DRIVE 20-30% LESS P.T.O. HORSE POWER.
Design material and/or Specifications are subject to Change without Notice and without Liability therefor.

SOLD BY



DOMRIES ENTERPRISES, INC.

12281 Road 29

Madera, California 93638

Phone (559) 673-9143 • FAX (559) 673-4110

Visit Our Website @ <http://www.domriesentinc.com>